



www.millersoils.co.uk

DATA SHEET: 7974

PRODUCT NAME/VISCOSITIES:

Suspension 10 NT+

DESCRIPTION:

Suspension 10 NT+ is a unique suspension fluid containing wear resistant additives to allow suspension performance to deliver at maximum potential. Also minimizes damping force variation over a large temperature range as well as providing a smoother ride.

APPLICATION:

The Suspension NT+ range has been designed to enhance the latest suspension systems. Tested by various racing teams has proved that the Suspension NT+ when put to the test, delivers every time. Our superior temperature stability provides an answer for one of the biggest challenges in competitive motorsport.

USER BENEFITS:

- The Suspension 10 NT+ has been specifically blended to provide fine tuned response and high levels performance for air, nitrogen and argon filled systems
- With other available grades such as: 2.5 NT+, 5 NT+, 7.5 NT+, 15 NT+, it is possible to cover all racing and climate conditions

TYPICAL CHARACTERISTICS:

Kinematic Viscosity @ 100°C	14.0 cSt
Kinematic Viscosity @ 40°C	54.3 cSt
Dynamic Viscosity @ -30°C	1375 mPa-s
Pour Point °C	-54°C
SAE Rating	5w40

HEALTH AND SAFETY:

Health and Safety Data Sheet 7974 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk

